

	<b>CALCIUM STEARATE</b>				<b>MLA</b> <b>GROUP</b>
	<b>M. L. A. INDUSTRIES, 111/230, HARSH NAGAR, KANPUR</b> Tel. : (0512)-2555292, Fax No. : 0512-2545548 E-mail: <a href="mailto:sales@mlagroup.com">sales@mlagroup.com</a> , <a href="mailto:mktg@mlagroup.com">mktg@mlagroup.com</a>				
<b>UNIFLOW</b>	Doc. No.:MLA/SPECS/07	Issue No.: 07	Issue Date: 10.3.2013	Replaces: issue dt 5.4.2007	

## CALCIUM STEARATE

**UNIFLOW** is a Calcium-Stearate manufactured by a novel semi-wet process developed by our in-house R & D department having tremendous experience in precipitation and particle size/morphology control technology. The output is a unique combination of lightness and melt transparency/stability in the product and better dispersion in the base polymer. The product is technically far better than the currently available products, besides the assurance of consistent quality from an ISO 9001:2000 certified unit.

### TYPICAL PHYSIO-CHEMICAL PROPERTIES

PROPERTY	UNIT	DLI-Petro
Colour & Appearance	-	White Free Flowing Powder
Bulk Density <sup>1,3</sup> – Loose – Compact*	gm/cc	0.15
		0.22
Moisture (105°C) <sup>2</sup>	%	<3.0
Electrolytes	%	<0.4
Residue on 300 mesh <sup>5</sup>	%	<0.2
Melting Point	°C	155±5
Melt Quality	--	Clear & Transparent
CaO	%	9-9.5
Ash content	%	9.2-9.8
Free fatty matter	%	<0.5
pH <sup>4</sup>	--	8.0-10.5

1) At the time of packing 2) By IR Moisture Balance 3) IS: 7589-1974 (A-8) 4) IS: 12076-1986(A-2) 5) IS: 2850-1983 (A-5.1)

This information and our technical advice-whether verbal, in writing or by way of trials are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sales and Delivery.

#### APPLICATION:

- As an acid scavenger in polymers processing
- As an internal lubricant in PVC and other polymers processing
- As a water repellent in paints and other coatings